



Program Power	-
Rated impedance	0 Ohm
Nominal diameter	0 mm
Sensitivity (2,83V/1m)	dB
Voice coil diameter	-
Frequency Range	500-20000 Hz

SPECIFICATIONS

Throat Diameter	0 mm
Rated Impedance	0 Ohm
Nominal Power Handling ¹	-
Program Power ²	0 W
Sensitivity ³	dB
Frequency Range ⁴	500-20000 Hz
Minimum Impedance	-
Phase Plug Material	-
Magnet Material	-
Diaphragm Material	-
Diaphragm Shape	-
Surround	-
Voice Coil Diam ⁵	-- 0 mm
Voice Coil Winding Material	-
Voice Coil Former Material	-
Flux Density	-
Ferrofluid	---
Connection type	-
Recommended Crossover Frequency	No

FREQUENCY RESPONSE AND IMPEDANCE CURVE ^{6 7}

T/S PARAMETERS

0 Ohm

Resonance frequency	Fs	-
DC Resistance	Re	Ohm
Total Q Factor	Qts	0
Mechanical Q Factor		0
Electrical Q Factor	Qes	0
Total Q Factor	Qts	0
Bl Factor	Bl	-
Effective Moving Mass	Mms	-
Suspension Compliance	Cms	-
Effective Piston Diameter	D	0 -
Effective piston area	Sd	0 - -
Voice Coil Inductance @ 1kHz	Le	-

NOTES

MOUNTING AND SHIPPING INFORMATION

Overall Diameter	209x330 mm - -
Total Depth	191 mm - 7,52 in
Bolt Circle Diameter	- - -
Bolt Holes Quantity and Diameter	6 / 6,3 mm - 0,25 in
Net Weight	1 Kg - 2,2 lb
Shipping Units	1 Pc